



Product Specification and Technical Data

PRODUCT: BG Universal Cooling System Cleaner

PART NO.: 540

TEST DATA:	Test	ASTM Test Method	Typical Test Results
	pH	D 1287	10.3
	Color	Visual	Green
	Specific Gravity	D 1122	1.074
	Density, lb/gal	Calc.	8.871
	Freezing Point	D 1177	-4.4°C (24°F)

PROBLEM: Typical in almost all automotive cooling systems is the eventual formation of rust, scale or other corrosion by-products. Even the slightest build-up of these materials on heat transfer surfaces can drastically affect the engine’s ability to shed heat and thus, decrease the overall effectiveness of the cooling system. Rust, oil and scale build-up will also restrict the flow of coolant through the system, causing overheating and possible engine damage.

SOLUTION: BG Universal Cooling System Cleaner provides superior removal of scale, oil, and harsh mineral deposits that form in the coolant system. When used as directed, BG Universal Cooling System Cleaner will remove tough residues that are caused by oil fouling, coolant inhibitor breakdown and glycol oxidation residues. BG Universal Cooling System Cleaner will also help solubilize and remove corrosion products, such as rust, that can hasten inhibitor depletion and increase corrosion of metal surfaces. The cooling system does not require neutralization after using BG Universal Cooling System Cleaner.

USAGE: Add one 12 ounce (355 mL) or 8 ounce (237 mL) bottle of BG Universal Cooling System Cleaner to cooling system. Operate engine until it reaches normal operating temperature. Continue operating engine for 10 to 30 minutes, keeping engine at normal operating temperature with heater controls at their highest position. Drain system and flush with clean water until system is free of rust. Refill with proper antifreeze and water concentration. BG Universal Cooling System Cleaner can be used in either gasoline or diesel engines. It contains no harsh chemicals and is harmless to all cooling system components. Do not leave in system.

NOTE: **For an added dose of superior rust and corrosion protection,** add 12 ounces (355 mL) BG Universal Super Cool[®], Part No. 546, to the system. The addition of BG Universal Super Cool[®] is highly recommended as it helps compensate for any untreated coolant left in the system after the service is performed.

BG Products, Inc. accepts no liability for excessive use or misuse of this product.