



Product Specification and Technical Data

PRODUCT: BG Stop Squeal

PART NO.: 860

TEST DATA: Test	ASTM Test Method	Typical Test Results
API Gravity @ 15.6°C (60°F)	D 287	41.7
Specific Gravity @ 15.6°C (60°F).	D 1298	0.8172
Density, U.S. lbs./gal. @ 15.6°C (60°F).	D 1250	6.813
Flash Point, COC	D 92	11°C (52°F)
Odor		Alcohol
Color	Visual.	Black

PROBLEM: One of the most frequent complaints of motorists is that of noisy, squealing brakes. Most brake noise is caused by vibrations that occur when pressure is applied.

SOLUTION: BG Stop Squeal is a safe and effective product for eliminating or preventing brake noise by impregnating the brake pad with ingredients that reduce sticking between the pad and rotor. When pressure is applied, the vibrations are significantly reduced, thus brake noise is stopped or is markedly less noticeable than before application of BG Stop Squeal.

TESTED: Testing was performed according to the Motor Vehicle Safety Standard No. 105-83, Hydraulic Brake Systems, Section S5.1.1.1. Test results proved that BG Stop Squeal has no detrimental effect on stopping distance.

USAGE: 1. SHAKE WELL before using. 2. If surface is glazed, buff before applying. 3. Saturate pads thoroughly. 4. Allow 10 to 15 minutes drying time. 5. DO NOT wipe. 6. Test brakes after re-assembly, before driving.

Recommended for use along with the BG Brake Lube, PN 608BK, to provide a Brake Maintenance Service.

BG Products, Inc. accepts no liability for excessive use or misuse of this product.